

# WhiteLED 36 Outdoor 15°

Output over **1650lm**  
**4800 lux at 2m** ^



LIDO/SDO is a compact and rugged LED based lighting fixture. With color temperature control, high CRI and high output LEDs, this fixture performs as an all-round, versatile tool. LIDO/SDO performs with an output of over 1600lm which makes it ideal for use in small-to-medium sized studios or stages.



## Specifications

IL-43658

Item	Specification	Details
Output	Lumens <sup>□</sup>	1650+
	Lux @ 2m ^	4800+
	Efficacy	31.94lm/W
	Max. Distance	25m
Light Source	LED Qty.	18 x Cool white, 18 x Warm white
	Drive current	350mA
Electrical	Input Voltage	100~240 VAC
	Power consumption	50W max. at full output
Control	On-board	Static color
	Control Protocol	DMX512
	Control Personality	CW, CW+D, STU1, STU2
Optical system	Dimmer	0-100%
	Strobe	0-20Hz
	Beam angle	15° (30°, 50° optional)
Physical	Dimensions	235x165x300mm
	Weight	4Kg
	Housing	Die-casting aluminum, powder-coated finish
	Color	Black/ Silver
	Fixture connection	Data in/out, Power in/out
	Cooling	Convection
Certification and Safety	Accessories #	Barn doors / top hat
	Certification	CE, ETL
	Environment	Dry/ Damp/ Wet Location IP67 (with LED display cover installed)
	Operation Temperature	-40°C ~50°C (operating) -20°C ~50°C (operating)



- Lumen measurements conforms to IES LM -79 -08
- ^ Measurement taken using standard optic
- # Accessories are sold separately

YG-LED304WW ARC-PAINT

15°

	2m	4m	6m	8m	10m	
LUX	3128	847	388	226.8	149.4	COOL WHITE
LUX	1781	466	216	128	87	WARM WHITE
LUX	4951	1320	602	350.7	236.7	CW+WW