

## Technical Specifications



June 1999





### MEASUREMENT MICROPHONE

#### FEATURES

- ▲ Sophisticated electret condenser measurement microphone
- ▲ Ultra-linear frequency response
- ▲ Evenly weighted, true omni-directional pattern
- ▲ Perfectly suited to room equalization applications
- ▲ Phantom powered, +15 V to +48 V
- ▲ Rugged construction and sleek, modern design
- ▲ Microphone stand adapter included
- ▲ Perfect for use with the ULTRA-CURVE DSP8000 / ULTRA-CURVE PRO DSP8024 or any other Real Time Analyzer

#### SPECIFICATIONS

Type	electret condenser, omni-directional
Impedance	600 Ohms
Sensitivity	- 60 dB
Bandwidth	15 Hz to 20 kHz
Connector	gold-plated XLR
Phantom power	+15 V to +48 V
Weight	approx. 120 g



BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

The information contained in this sheet is subject to change without notice. No part of this sheet may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER GmbH.

ALL RIGHTS RESERVED © 1999 BEHRINGER. BEHRINGER is a registered trademark.  
 BEHRINGER INTERNATIONAL GmbH, Hanns-Martin-Schleyer-Str. 36-38, D-47877 Willich-Münchheide II  
 Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30



www.behringer.de