



Obey 40 D-Fi 2.4

The Obey 40 D-Fi 2.4 is a small, but full-featured lighting controller with a built-in D-Fi transmitter so you can built a rig without long DMX cable runs! The Obey 40 D-Fi 2.4 works with any D-Fi compatible product and controls up to 12 different types of lights. It stores scenes and chases for playback, and it operates lights "on the fly". The stored scenes and chases are triggered by sound, or manually adjusted, to get just the right speed and fade time for your look. The Obey 40 D-Fi 2.4 is MIDI compatible and has dedicated fog and strobe controls. The Obey 40 D-Fi 2.4 is the perfect board for creating a dazzling light show without long cable runs! And it travels smartly in the CHAUVET DJ [CHS-30 Gear Bag](#).

Highlights

- Wireless DMX controller capable of programming any DMX product
- Easily send wireless DMX signals across the room using the built-in D-Fi 2.4GHz transmitter
- Individually control up to 12 different lights
- Customize looks with adjustable strobe and fade effects, audio sensitivity and fade times for all playback modes
- Increase effects with fog and strobe control, reversible sliders, beat activation, tap-sync and auto run
- Ability to grab any fixture on the fly, reassign channels and sequentially link chases
- Increase flexibility with MIDI triggerable chases and scenes
- Conveniently fits in a standard 3-space (3U) mounting rack
- Fits best in the CHS-30 VIP Gear Bag

Specifications

- DMX Channels: 192
- DMX Connectors: 3-pin XLR
- Max Unobstructed Distance: 656 ft (200 m)
- Operating Frequency: 2.433 to 2.48 GHz
- Antenna Connection: RP-SMA
- Input Voltage: 9 VDC, 500 mA (external power supply: 100 to 240 VAC, 50/60 Hz)
- Power and Current: 3 W, 0.1 A @ 120 V, 60 Hz 2 W, 0.1 A @ 230 V, 50 Hz
- Weight: 5.2 lb (2.4 kg)
- Size: 19 x 6.7 x 3.5 in (483 x 171 x 89 mm)
- Approvals: CE, FCC
- Programmable Scenes: 240
- Programmable Banks: 30

What's Included

- External power supply
- User Manual
- Warranty card