

# SQ-5016

## UHF 16-freq wireless handheld microphone

### General Features

- 16 factory preset user-selectable UHF frequencies from 600-900 MHz per 20 MHz bandwidth.
- $\pm 40$  KHz peak deviation.
- Pilotone Control.
- Very low spurious emission passed the stringent CE & FCC regulations.
- Changeable dynamic or condenser microphone capsule.
- No handling noise in handheld with condenser capsule.
- Handheld housing coated with rubberized paint for smooth holding.
- Low current consumption.
- Up to 16 hours of operation with 2 AA Alkaline batteries.
- Color ring on handheld microphone identifies channel.
- Matching battery charger: HC-30

### Specifications

Model	SQ-5016
Frequency Range	UHF 500-900 MHz
Switching Bandwidth	20 MHz
Switchable Frequency	16
RF Power Output	< 35mW**
Spurious Emission	> 60 dB below carrier
Dynamic Range	> 110 dB
Display Screen	LCD
T.H.D	< 0.5%
Peak Deviation	$\pm 40$ KHz
Antenna	Built in
Battery Type	AA*2
Operating Life (Alkaline)	16 hours
Charging Function	Yes
Battery charger	HC-30
Microphone Capsule	Dynamic or condenser type
Dimension (mm)	$\phi 46 \times 240$
Weight (g)	200

Remark: The above specifications are subject to change without prior notice.

\*\* The output power may vary from country to country.

