



PAR 56

300PAR56/MFL 240V

18677

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent









Product data

GX16d
PAR
Aluminized
177.8
127
623
692
General Electric (GE)
E

Performance data

Nominal correlated colour temperature (CCT) [K]	2750
Nominal beam angle [°]	21
Nominal lumens [lm]	3450
Rated Life [h]	2000
Nominal power [W]	300
Weighted energy consumption [kWh/1000h]	285.58
Nominal lamp voltage [V]	245

Electrical data

Coil type	CC-13
Ballast Required	No





Logistic data

DUN Code	00043168186773
EAN Code	0043168186773
Pack Quantity	12
Layer quantity	64 EUR, 88 UK
Layer quantity EUR	64
Layer quantity UK	88
Pallet quantity EUR (PC)	192
Pallet quantity UK (PC)	264
Outer case size	349 x 300 x 446 (mm)
Product status	Available

Application areas



Disclaimer

Special purpose lamp - Stage Studio. Not suitable for household illumination.