

CONTROL[®] 2P

COMPACT POWERED REFERENCE MONITOR



PROFESSIONAL



CONTROL[®] 2P

COMPACT POWERED REFERENCE MONITOR



CONTROL 2P

Includes

One(1) Control 2P Powered Master Speaker
and One(1) Control 2P Extension Speaker

Included Accessories

Extension Speaker Wire with
right-angle 1/4" plug.
Power Supply
Two (2) Snap-On Pedestals
Users Guide

CONTROL 2PM

Includes

One(1) Control 2P Powered Master Speaker

Included Accessories

Power Supply
One (1) Snap-On Pedestal


Optional Accessories

MTC-2P Wall Mount Kit
Includes two Wall Mount Brackets,
and one Power Supply Holder.

Perfect for all
APPLICATIONS



Digital Editing



Entertainment Installations



AV Presentations



Electronic Musical Instruments



FEATURES

STUDIO QUALITY TRANSDUCERS FOR ACCURACY, AND RICH BASS RESPONSE: 80 HZ - 20 KHZ

35 WATT PER-CHANNEL POWER AMPLIFIER AND HIGH SENSITIVITY DRIVERS PRODUCE EXCEPTIONAL OUTPUT: 115 DB MAX SPL PER PAIR.

BALANCED XLR, AND UNBALANCED RCA INPUTS ALLOW CONNECTION TO A RANGE OF SIGNAL SOURCES.

STEREO HEADPHONE JACK ALLOWS MONITORING USING HEADPHONES.

ERGONOMIC, SIDE-MOUNTED VOLUME CONTROL - SIMULTANEOUSLY CONTROLS LEFT AND RIGHT SPEAKERS.

HIGH FREQUENCY ADJUST CONTROL - ALLOWS THE USER TO CONTOUR HF RESPONSE TO APPLICATION REQUIREMENTS.

MAGNETICALLY-SHIELDED TRANSDUCERS FOR USE NEAR CRT MONITORS AND MAGNETICALLY SENSITIVE EQUIPMENT.

INTERNAL PEAK LIMITER AND OVERLOAD PROTECTION CIRCUIT - PROTECTS THE SYSTEM FROM DAMAGE CAUSED BY CONTINUOUS OVER-DRIVING.

WALL-MOUNT CAPABLE USING OPTIONAL MTC-2P MOUNTING KIT.

INCLUDED SNAP-ON PEDESTALS OPTIMIZE LISTENING ANGLE FOR DESK TOP APPLICATIONS.

SPECIFICATION

| | |
|--------------------------------------|--|
| Frequency Range: | 80 Hz - 20 kHz |
| Maximum SPL Per Pair: | 115 dB |
| Maximum SPL Master Only: | 111 dB |
| LF Transducer: | 135 mm (5.25 in) low frequency loudspeaker |
| HF Transducer: | 19 mm (.75 in) polycarbonate dome tweeter |
| Crossover Frequency: | 4.2 kHz |
| Input Sensitivity: | +4 dBu XLR 1/4"; 0 dBu RCA |
| Signal Input Connectors (x2): | Balanced Neutrik [®] Combo XLR 1/4" TRS; Unbalanced RCA |
| Amplifier Power: | 35 Watts continuous per-channel |
| Power Requirements: | 19 V DC / 3.42 A - use only supplied power supply |
| Headphone Jack: | 3.5 mm (1/8") |
| Dimensions: | 235 x 159 x 143 mm (9.3 x 6.3 x 5.6 in) |
| Net Weight Master Speaker: | 2.6 kg (5.5 lb) |
| Net Weight Extension Speaker: | 2.2 kg (4.5 lb) |

* Neutrik and the names of Neutrik products referenced herein are either trademarks and/or service marks of Neutrik.