



www.lightemotion.com.au

LEDBAR



Features

- 4-channel DMX-512 LED cyclorama light
- Blackout/static/dimmer/strobe
- Operating modes:
 - Blackout and static / flashing colors
 - RGB color mixing
 - Color fade
- Static colors and RGB color mixing with or without DMX controller
- Built-in automated programs via master/slave or DMX
- Built-in sound active programs via master/slave or DMX

Additional Features

- Linkable with COLORbank™ LED
- Additional power output for daisy chaining units together
- Master/slave mode with additional output for daisy chaining
 - Allows for color-changing runway effect (up to 31 units)
- Sound sensitivity knob
- Low power consumption

Optional Controller

- LED Bar™ Foot Controller (LED-FS1)

Technical Specifications

WEIGHT & DIMENSIONS

Length..... 38 in (965 mm)
Width2.5 in (64 mm)
Height6 in (152 mm)
Weight 4.5 lbs (9.1 kg)

POWER

Auto-switching power supply..... 100-240V 50/60Hz
Power Consumption 33.3W (.39A) max at 120V
Inrush Power 24.6W (.33A) at 120V
Power Factor70 at 120V
Power Output (AC Plug)..... 8A (960W at 120V) max

LIGHT SOURCE

LED.....384 Total (128 red, 128 green, 128 blue) 100,000 hour

PHOTO OPTIC

Beam Angle..... 63° x 29°
Field Angle..... 82° x 52°

THERMAL

Maximum ambient temperature..... 104°F (40°C)

FUSE

Main..... 1.5A 250V fast blow

CONTROL & PROGRAMMING

Data input locking 3-pin XLR male socket
Data output..... locking 3-pin XLR female socket
Data pin configuration pin 1 shield, pin 2 (-), pin 3 (+)
Protocols..... DMX-512 USITT
DMX Channels4

ORDERING INFORMATION

LED Bar™LED Bar

WARRANTY INFORMATION

Warranty 2-year limited warranty