



evolutionwireless 

EM 100



Contents

Important safety instructions	2
The EM 100 G3 stationary receiver	4
Areas of application	4
The frequency bank system	5
Delivery includes	7
Product overview	8
Overview of the EM 100 G3 receiver	8
Overview of the displays	9
Putting the receiver into operation	11
Preparing the receiver for use	11
Connecting an amplifier/mixing console	17
Connecting the mains unit	18
Using the receiver	19
Switching the receiver on/off	19
Synchronizing a transmitter with the receiver	20
Deactivating the lock mode temporarily	22
Muting the audio signal	23
Selecting a standard display	24
Using the operating menu	25
The buttons	25
Overview of the operating menu	26
Working with the operating menu	28
Adjustment tips and functions	30
Standard displays with additional functions	30
The main menu "Menu"	33
The extended menu "Advanced Menu"	38
Synchronizing transmitters with receivers	42
Synchronizing a transmitter with the receiver – individual operation	42
Synchronizing transmitters with receivers – multi-channel operation	43
Cleaning the receiver	45
Recommendations and tips	46
If a problem occurs	47
Accessories and spare parts	49
Specifications	51
Manufacturer Declarations	54
Index	56



An animated instruction manual can be viewed on the EM 100 G3 product page on our website at www.sennheiser.com.

Important safety instructions

- Read this instruction manual.
- Keep this instruction manual. Always include this instruction manual when passing the product on to third parties.
- Heed all warnings and follow all instructions in this instruction manual.
- Only clean the product when it is not connected to the mains. Use a cloth for cleaning.
- Refer all servicing to qualified service personnel.
Servicing is required if the product has been damaged in any way, liquid has been spilled, objects have fallen inside, the product has been exposed to rain or moisture, does not operate properly or has been dropped.
- **WARNING:** To reduce the risk of short circuits, do not use the product near water and do not expose it to rain or moisture. Do not place objects filled with liquids, such as vases or coffee cups, on the product.
- Only use the supplied mains unit.
- Unplug the mains unit from the wall socket
 - to completely disconnect the product from the mains,
 - during lightning storms or
 - when unused for long periods of time.
- Only operate the mains unit from the type of power source specified in the chapter “Specifications” (see page 51).
- Ensure that the mains unit is
 - in a safe operating condition and easily accessible,
 - properly plugged into the wall socket,
 - only operated within the permissible temperature range,
 - not covered or exposed to direct sunlight for longer periods of time in order to prevent heat accumulation (see “Specifications” on page 51).
- Do not block any ventilation openings. Install the product in accordance with the instructions given in this instruction manual.
- Do not install the product near any heat sources such as radiators, stoves, or other devices (including amplifiers) that produce heat.
- Only use attachments/accessories specified by Sennheiser.

Overloading

Do not overload wall outlets and extension cables as this may result in fire and electric shock.

Replacement parts

When replacement parts are required, be sure the service technician uses replacement parts specified by Sennheiser or those having the same characteristics as the original part. Unauthorized substitutions may result in fire, electric shock, or other hazards.

Danger due to high volumes

This product is capable of producing sound pressure exceeding 85 dB(A). 85 dB(A) is the sound pressure corresponding to the maximum permissible volume which is by law (in some countries) allowed to affect your hearing for the duration of a working day. It is used as a basis according to the specifications of industrial medicine. Higher volumes or longer durations can damage your hearing. At higher volumes, the duration must be shortened in order to prevent hearing damage. The following are sure signs that you have been subjected to excessive noise for too long a time:

- You can hear ringing or whistling sounds in your ears.
- You have the impression (even for a short time only) that you can no longer hear high notes.

Intended use

Intended use of the ew 100 G3 series products includes:

- having read these instructions especially the chapter "Important safety instructions",
- using the products within the operating conditions and limitations described in this instruction manual.

"Improper use" means using the products other than as described in this instruction manual, or under operating conditions which differ from those described herein.

The EM 100 G3 stationary receiver



This receiver is part of the evolution wireless series generation 3 (ew G3). With this series, Sennheiser offers high-quality state-of-the-art RF transmission systems with a high level of operational reliability and ease of use. Transmitters and receivers permit wireless transmission with studio-quality sound.

Features of the evolution wireless 100 G3 series:

- Optimized PLL synthesizer and microprocessor technology
- **HDX** noise reduction system
- Pilot tone squelch control
- True diversity technology
- Switching bandwidth of 42 MHz
- Scan function (Easy Setup) for scanning the frequency banks for unused channels

Areas of application

The receiver can be combined with the following optional components of the ew G3 series (see "Accessories and spare parts" on page 49):


Receiver	Transmitters	Combinable with
	SK 100 G3 	<ul style="list-style-type: none"> • Clip-on microphones: ME 2, ME 4 • Headmic: ME 3 • Instrument cable: CI 1
	SKM 100 G3 	Interchangeable microphone heads: <ul style="list-style-type: none"> • MMD 835-1, MMD 845-1 • MME 865-1

The devices are available in the same UHF frequency ranges and are equipped with the same frequency bank system with factory-preset frequencies. An advantage of the factory-preset frequencies is that


- a transmission system is ready for immediate use after switch-on,
- several transmission systems can be operated simultaneously on the preset frequencies without causing intermodulation interference.

The frequency bank system

The receiver is available in 6 UHF frequency ranges with 1,680 frequencies per frequency range:



Each frequency range (A–E, G) offers 21 frequency banks with up to 12 channels each:



Each of the channels in the frequency banks “1” to “20” has been factory-preset to a fixed frequency (frequency preset).

The factory-preset frequencies within one frequency bank are intermodulation-free. These frequencies cannot be changed.

For an overview of the frequency presets, please refer to the supplied frequency information sheet. Updated versions of the frequency information sheet can be downloaded from the EM 100 G3 product page on our website at www.sennheiser.com.

The frequency bank “U” allows you to freely select and store frequencies. It might be that these frequencies are **not** intermodulation-free (see page 44).


Delivery includes

The packaging contains the following items:

- 1 EM 100 G3 stationary receiver
- 1 NT 2-3 or NT 2-1 mains unit with one country adapter
- 2 rod antennas
- 2 stacking elements
- 1 instruction manual
- 1 frequency information sheet
- 4 device feet

Product overview

Overview of the EM 100 G3 receiver



A Operating elements – front panel


- 1 sync button
- 2 Infra-red interface
- 3 Display panel, backlit in orange
- 4 SET button
- 5 UP/DOWN button
- 6 STANDBY button;
ESC function (cancel)

B Operating elements – rear panel

- 7 Cable grip for power supply DC cable
- 8 DC socket (DC IN) for connection of NT 2 mains unit
- 9 Audio output (AF OUT BAL), XLR-3M socket, balanced
- 10 Audio output (AF OUT UNBAL), 1/4" (6.3 mm) jack socket, unbalanced
- 11 Service interface (DATA)
- 12 Service interface (DATA)
- 13 Antenna input II (ANT II) with remote power supply input, BNC socket
- 14 Type plate
- 15 Antenna input I (ANT I) with remote power supply input, BNC socket

Overview of the displays

After switch-on, the receiver displays the standard display “Receiver Parameters”. For further illustrations and examples of the different standard displays, please refer to page 24. This standard display displays the operating states of the receiver.



Display	Meaning
① RF level “RF” (Radio Frequency)	<p>Diversity display:</p> <p>I I Antenna input I is active</p> <p>I I Antenna input II is active</p> <p>RF signal level: Field strength of the received signal</p> <p>Squelch threshold level</p>
② Audio level “AF” (Audio Frequency, see page 36)	<p>Modulation of the transmitter with peak hold function</p> <p>When the display for audio level shows full deflection, the audio level is excessively high. When the transmitter is overmodulated frequently or for extended periods of time, the “PEAK” display is shown inverted.</p>
③ Frequency bank and channel (see page 35)	Current frequency bank and channel number
④ Frequency (see page 35)	Current receiving frequency
⑤ Name (see page 36)	Freely selectable name of the receiver

Display	Meaning
⑥ Pilot tone "P" (see page 40)	Activated pilot tone evaluation
⑦ Muting function "MUTE" (see page 23)	Audio signal is muted (see also page 47)
⑧ Battery status of the transmitter	<p>Charge status:</p> <ul style="list-style-type: none">  approx. 100%  approx. 70%  approx. 30%  icon is flashing; charge status is critical
⑨ Lock mode icon (see page 37)	Lock mode is activated

Putting the receiver into operation

Preparing the receiver for use



Recommendations for optimum reception

To ensure optimum reception even under difficult conditions, we recommend connecting remote antennas and, if necessary, using antenna splitters (see "Accessories and spare parts" on page 49).

When rack-mounting the receiver, you can mount the supplied antennas to the front of the rack by using an antenna front mount kit. When mounting more than one receiver into a rack, you should use remote antennas.

If you want to mount the receiver [into a 19" rack](#):

- ▶ Read the corresponding chapter on page 13.

If you want to set up the receiver [on a flat surface](#):

- ▶ Read the next chapter.

Setting up the receiver on a flat surface

CAUTION!

Risk of staining of furniture surfaces!

Some furniture surfaces have been treated with varnish, polish or synthetics which might cause stains when they come into contact with other synthetics. Despite a thorough testing of the synthetics used by us, we cannot rule out the possibility of staining.

- ▶ Do not place the receiver on delicate surfaces.


Fastening the stacking elements



The stacking elements are designed to help protect the operating elements from damage or deformation, e.g. if the receiver is dropped. Therefore, fasten the stacking elements, even if you do not want to stack your receivers.

To fasten the stacking elements 16:

- ▶ Unscrew and remove the two recessed head screws (M4x8) on each side of the receiver (see left-hand diagram).
- ▶ Secure the stacking elements 16 to the sides of the receiver using the previously removed recessed head screws (see right-hand diagram).




Fitting the device feet



If you want to stack receivers (see next section), only fit the device feet to the base of the lowermost receiver.

Do not fit the device feet when mounting the receiver into a 19" rack.



- ▶ Clean the base of the receiver where you want to fix the device feet.
- ▶ Fit the device feet to the four corners of the receiver as shown.
- ▶ Place the receiver on a flat, horizontal surface.

Stacking receivers

You can stack several receivers on top of each other.


CAUTION!



Danger of injury due to toppling receiver stacks!

High receiver stacks can easily topple over.


- ▶ Place the stack on an absolutely flat surface.
- ▶ Secure the stack against toppling over.
- ▶ Fasten the stacking elements as described in the previous section.
- ▶ Stack the receivers so that the recesses of the stacking elements completely engage with each other.



Connecting the rod antennas

The supplied rod antennas 17 can be mounted quickly and easily and are suitable for all applications where – good reception conditions provided – a wireless transmission system is to be used without a large amount of installation work.

- ▶ Connect the two rod antennas 17 to the BNC sockets 13 and 15 at the rear of the receiver.



- ▶ Align the rod antennas upwards in a V-shape.



When using more than one receiver, we recommend connecting remote antennas and, if necessary, using Sennheiser antenna accessories. For more information, visit the ew G3 product page at www.sennheiser.com.

Mounting the receiver into a 19" rack



Do not mount the stacking elements and do not fit the rubber feet when mounting the receiver into a 19" rack.

CAUTION!



Risks when rack mounting the receiver!


When installing the device in a closed or multi-rack assembly, please consider that, during operation, the ambient temperature, the mechanical loading and the electrical potentials will be different from those of devices which are not mounted into a rack.

- ▶ Make sure that the ambient temperature within the rack does not exceed the permissible temperature limit specified in the specifications (see page 51).
- ▶ Ensure sufficient ventilation; if necessary, provide additional ventilation.
- ▶ Make sure that the mechanical loading of the rack is even.
- ▶ When connecting to the power supply, observe the information indicated on the type plate. Avoid circuit overloading. If necessary, provide overcurrent protection.
- ▶ When rack mounting, please note that intrinsically harmless leakage currents of the individual mains units may accumulate, thereby exceeding the allowable limit value. As a remedy, ground the rack via an additional ground connection.


Rack mounting one receiver

To mount the receiver into a rack, you require the GA 3 rack adapter (see "Accessories and spare parts" on page 49):

- ▶ Secure the rack mount "ears" 20 of the GA 3 rack adapter to the receiver in the same way as described for the stacking elements (see page 11).
- ▶ Secure the blanking plate 21 of the GA 3 rack adapter to one of the rack mount "ears" 20 using two recessed head screws (M 6x10).



- ▶ Connect the antennas. You have the following options:
 - You can connect the supplied rod antennas 17 to the rear of the receiver (see page 13). In this case, insert the two blanking plates 23 into the holes of the blanking plate.
 - You can use the AM 2 antenna front mount kit (see “Accessories and spare parts” on page 49) and mount the rod antennas to the blanking plate 21.



i When using more than one receiver, we recommend connecting remote antennas and, if necessary, using Sennheiser antenna accessories. For more information, visit the ew G3 product page at www.sennheiser.com.

To mount the receiver into a 19" rack:

- ▶ Slide the receiver with the mounted blanking plate 21 into the 19" rack.
- ▶ Secure the rack mount "ears" 20 to the 19" rack.

If you are using the supplied rod antennas:

- ▶ Align the antennas in a V-shape to obtain the best possible reception.


Rack mounting two receivers

i When rack mounting two receivers side by side, you can only front mount the antennas when using the ASA 1 antenna splitter in conjunction with the AM 2 antenna front mount kit and an additional GA 3 rack adapter (see “Accessories and spare parts” on page 49).

We recommend using remote antennas.

To mount the receivers into a rack using the GA 3 rack adapter:

- ▶ Place the two receivers side by side upside-down onto a flat surface.



- ▶ Secure the jointing plate 22 to the receivers using six recessed head screws (M 3x6).

The rack mount "ears" are mounted instead of the stacking elements:

- ▶ Secure the rack mount "ears" to the receivers in the same way as described for the stacking elements (see page 11).


To mount the antennas:

- ▶ Use remote antennas, if necessary in conjunction with the ASA 1 antenna splitter (see "Accessories and spare parts" on page 49).

To mount the receivers into the rack:

- ▶ Slide the receivers into the 19" rack.
- ▶ Secure the rack mount "ears" to the 19" rack.

Connecting an amplifier/mixing console




The receiver's 1/4" (6.3 mm) jack socket **10** and XLR-3M socket **9** are connected in parallel, allowing you to simultaneously connect two devices (e.g. amplifier, mixing console) to the receiver.

- ▶ Use a suitable cable to connect the amplifier/mixing console to the 1/4" (6.3 mm) jack socket **10** or the XLR-3M socket **9**.



For detailed information on balanced and unbalanced connection, please refer to the chapter "Connector assignment" on page 53.

Connecting the mains unit



Only use the supplied NT 2-3 or NT 2-1 mains unit. It is designed for your receiver and ensures safe operation.

To connect the mains unit:

- ▶ Connect the yellow connector of the mains unit 18 to the yellow socket 8 at the rear of the receiver.
- ▶ Pass the cable of the mains unit through the cable grip 7.
- ▶ Slide the supplied country adapter 19 onto the mains unit 18.
- ▶ Plug the mains unit 18 into a wall socket.

Using the receiver

To establish a transmission link, proceed as follows:

1. Switch the receiver on (see next section).
2. Switch the transmitter on (see the instruction manual of the transmitter).
The transmission link is established and the receiver's RF level display "RF" reacts.




It is vital to observe the notes on frequency selection on page 42.

If you cannot establish a transmission link between transmitter and receiver:

- ▶ Make sure that transmitter and receiver are set to the same frequency bank and to the same channel.
- ▶ Read the chapter "Synchronizing transmitters with receivers" on page 42 and, if necessary, the chapter "If a problem occurs ..." on page 47.

Switching the receiver on/off



To switch the receiver on:



- ▶ Briefly press the **STANDBY** button **6**.
The receiver switches on and the "Receiver Parameters" standard display appears.

To switch the receiver to **standby mode**:

- ▶  Keep the **STANDBY** button **6** pressed until **"OFF"** appears on the display panel.
The receiver switches to standby mode.



When in the operating menu, pressing the **STANDBY** button **6** will cancel your entry (ESC function) and return you to the current standard display.

To completely switch the receiver **off**:

- ▶ Disconnect the receiver from the mains by unplugging the mains unit from the wall socket.

Synchronizing a transmitter with the receiver

You can synchronize a suitable transmitter of the ew 100 G3 series with the receiver. During synchronization, the following parameters are transferred to the transmitter:


Setting	Transferred parameters
"Frequency Preset"	Currently set frequency
"Name"	Freely selectable name currently set on the receiver
"Pilot Tone"	Current pilot tone setting of the receiver ("Inactive"/"Active")



It is vital to observe the notes on frequency selection on page 42.

To transfer the parameters:

- ▶ Switch the transmitter and the receiver on.



- ▶ Press the **sync** button **1** on the receiver. "Sync" appears on the display panel of the receiver.
- ▶ Place the infra-red interface of the transmitter (see the instruction manual of the transmitter) in front of the infra-red interface **2** of the receiver.
The parameters are transferred to the transmitter. When the transfer is completed, "✓" appears on the receiver's display panel. The receiver then switches back to the current standard display.

To cancel the transfer:

- ▶ Press the **STANDBY** button **6** on the receiver. "X" appears on the display panel of the receiver. "X" also appears if no suitable transmitter was found.

Deactivating the lock mode temporarily

You can activate or deactivate the automatic lock mode via the “Auto Lock” menu item (see page 37).

If the lock mode is activated, you have to temporarily deactivate it In order to be able to operate the receiver:

-  ▶ Press the **SET** button.
“Locked” appears on the display panel.
-  ▶ Press the UP/DOWN button.
“Unlock?” appears on the display panel.
-  ▶ Press the **SET** button.
The lock mode is temporarily deactivated:

When you are in the operating menu

The lock mode remains deactivated until you exit the operating menu.

When one of the standard displays is shown

The lock mode is automatically activated after 10 seconds.

The lock mode icon  flashes prior to the lock mode being activated again.



Muting the audio signal

To **mute** the audio signal:

-  ▶ When one of the standard displays is shown on the display panel, press the **STANDBY** button.
“RX Mute On?” appears on the display panel.
-  ▶ Press the **SET** button.
The audio signal is muted.


To **unmute** the audio signal:

-  ▶ Press the **STANDBY** button.
“RX Mute Off?” appears on the display panel.
-  ▶ Press the **SET** button.
The muting is canceled.

If “RX Mute On?” or “RX Mute Off?” appears on the display panel but you do not wish to change the status of the muting function:

-  ▶ Press the **STANDBY** button.
The status of the muting function remains unchanged and the current standard display appears.

Selecting a standard display



▶ Press the UP/DOWN button **5** to select the standard display:

Contents of the display	Selectable standard display
	“Receiver Parameters” appears after switch-on of the receiver and displays the receiver parameters (see page 9)
	“Soundcheck” (display with additional function) displays the signal quality within the transmission area (see page 30)
	“Guitar Tuner” * (display with additional function) displays the guitar tuner (see page 30)

* The **“Guitar Tuner”** standard display is deactivated upon delivery. To show this standard display, you have to activate it (see page 39).


Using the operating menu

A special feature of the Sennheiser ew G3 series is the consistent, intuitive menu structure of transmitters and receivers. As a result, adjustments to the settings can be made quickly – even in stressful situations, for example on stage or during a live show or presentation.

The buttons

Button	Function of the button
Press the STANDBY button 	<ul style="list-style-type: none"> • Switches the receiver on and off • Cancels the entry and returns to the current standard display (ESC function) • Mutes the receiver (special function, see page 23)
Press the SET button 	<ul style="list-style-type: none"> • Changes from the current standard display to the operating menu • Calls up a menu item • Enters a submenu • Stores the settings and returns to the operating menu
Press the UP/DOWN button 	<ul style="list-style-type: none"> • Selects a standard display (see page 24) • Changes to the next/previous menu item • Changes the setting of a menu item

Overview of the operating menu



Display	Function of the menu item	Page
Main menu "Menu"		
Squelch	Adjusts the squelch threshold	33
Easy Setup	Scans for unused frequency presets, releases and selects frequency presets	34
Frequency Preset	Sets the frequency bank and the channel	35
Name	Enters a freely selectable name	36
AF Out	Adjusts the audio output level	36
Equalizer	Changes the frequency response of the output signal	37
Auto Lock	Activates/deactivates the automatic lock mode	37
Advanced	Calls up the extended menu " Advanced Menu "	38
Exit	Exits the operating menu and returns to the current standard display	–
"Easy Setup"		
Reset List	Releases all locked frequency presets	34
Current List	Selects an unused frequency preset	
Scan New List	Scans for unused receiving frequencies (frequency preset scan)	
Exit	Exits " Easy Setup " and returns to the main menu	–

Display	Function of the menu item	Page
Extended menu "Advanced Menu"		
Tune	Sets the transmission frequencies for the frequency bank "U"	38
	Sets the channel and the receiving frequency for the frequency bank "U"	39
Guitar Tuner	Selects the mode of the guitar tuner function	39
Pilot Tone	Activates/deactivates the pilot tone evaluation	40
LCD Contrast	Adjusts the contrast of the display panel	41
Reset	Resets the settings made in the operating menu	41
Software Revision	Displays the current software revision	41
Exit	Exits the extended menu "Advanced Menu" and returns to the main menu	–

Working with the operating menu



If the lock mode is activated, you have to deactivate it in order to be able to work with the operating menu (see page 22).

By way of example of the “Frequency Preset” menu item, this section describes how to use the operating menu.


Changing from a standard display to the operating menu

-  Press the **SET** button.
-  The current standard display is replaced by the main menu. The last selected menu item is displayed.


Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

Selecting a menu item

-  Press the UP/DOWN button to change to the “Frequency Preset” menu item. The current setting of the menu item is displayed:



Changing and storing settings



-  Press the **SET** button to call up the menu item.
-  Press the UP/DOWN button to set the frequency bank.
-  Press the **SET** button to confirm your selection.
-  Press the UP/DOWN button to set the channel.
-  Press the **SET** button to store the setting.

Canceling an entry

- ▶ Press the **STANDBY** button to cancel an entry.
The current standard display appears on the display panel.

To subsequently return to the last edited menu item:

- ▶ Press the **SET** button repeatedly until the last edited menu item appears.

Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

Exiting a menu item

- ▶ Change to the “**Exit**” menu item.
- ▶ Confirm your selection.
You return to the next higher menu level.

To directly return to the current standard display:

- ▶ Press the **STANDBY** button.


Adjustment tips and functions

The operating menu allows you to make settings for your receiver and your transmitters. The “**Guitar Tuner**” and “**Soundcheck**” standard displays provide additional functions and can be called up by pressing the UP/DOWN button, without having to get into the operating menu.

Standard displays with additional functions

Tuning a guitar (SK transmitters only)

- ▶ Activate the “**Guitar Tuner**” standard display via the operating menu (see page 39).
- ▶ Connect a guitar to your SK transmitter.
- ▶ On the receiver, change to the “**Guitar Tuner**” standard display (see page 24).



- ▶ Tune your guitar.
The receiver automatically recognizes the pitch of the plucked string.
For more information on the “**Guitar Tuner**” menu item, refer to page 39.


Doing a soundcheck

By doing a soundcheck, you can check the reception area for field strength gaps (“dropouts”) which cannot be compensated for by the receiver’s diversity circuitry.




The “**Soundcheck**” standard display must not be activated until later because otherwise the recording will give wrong results.

- ▶ If necessary, change from the “**Soundcheck**” standard display to one of the other standard displays of your receiver.




- ▶ Position the transmitter in the area in which it is to be used and switch it on.
- ▶ Leave the transmitter switched on and go to your receiver.
- ▶ On the receiver, change to the "Soundcheck" standard display.



If no transmitter is being received or if the signal is below the squelch threshold level, "MUTE" appears on the display panel (see "If a problem occurs ..." on page 47).

- ▶ Go to your transmitter.
- ▶ With the transmitter, walk up and down the area in which it is to be used.
- ▶ Then leave the transmitter there and do **not** switch it off.

During the soundcheck, the receiver records the RF level and the AF level. The recording result is displayed on the "Soundcheck" standard display:



Display	Meaning	What to do ...
RF Min	Min. RF signal level: must be well above the squelch threshold level for one of the two antennas	<ul style="list-style-type: none"> ▶ Check if the antennas and the antenna cables are correctly connected. ▶ Improve the position of the antennas. ▶ If necessary, use antenna boosters.
RF Max	Max. RF signal level: both antennas should reach 40 dB μ V	<ul style="list-style-type: none"> ▶ On your transmitter, adjust the audio level as high as possible without the level display for audio level showing full deflection (AF Max is at a level with the PEAK display). <p>For more information, refer to the instruction manual of the transmitter.</p>
AF Max	Max. audio level	<ul style="list-style-type: none"> ▶ On your transmitter, adjust the audio level as high as possible without the level display for audio level showing full deflection (AF Max is at a level with the PEAK display). <p>For more information, refer to the instruction manual of the transmitter.</p>


If only one or none of the diversity displays is displayed during the sound check:

- ▶ Check if the antennas are properly positioned or check the antenna cables.




Both diversity displays can only be displayed on the "Soundcheck" standard display. During normal operation of the receiver, only one of the diversity displays is displayed.

The main menu “Menu”



Adjusting the squelch threshold



Adjustment range: “Low”, “Middle”, “High”, can be switched off

The squelch eliminates annoying noise when the transmitter is switched off. It also suppresses sudden noise when there is no longer sufficient transmitter power received by the receiver.

- ▶ Adjust the squelch threshold – with the transmitter switched off – to the lowest possible setting that suppresses hissing noise.



In der Einstellung „High“ der Rauschsperrschwelle wird die Reichweite der Übertragungsstrecke unter ungünstigen Empfangsbedingungen verringert.

CAUTION!



Danger of hearing damage and material damage!

If you switch the squelch off or adjust the squelch threshold to a very low value, loud hissing noise can occur in the receiver. The hissing noise can be loud enough to cause hearing damage or overload the loudspeakers of your system!

- ▶ Always make sure that the squelch is switched on (see below).
- ▶ Before adjusting the squelch threshold, set the volume of the audio output level (“AF Out”, see page 36) to the minimum.
- ▶ Never change the squelch threshold during a live transmission.

The squelch should only be switched off for servicing purposes werden. With the squelch threshold set to “Low”, you switch the squelch off by keeping the DOWN button pressed for 3 seconds.

Display	Squelch is ...
	<p>... switched on</p> <p>The dotted line displays the squelch threshold.</p>
	<p>... switched off.</p> <p>The dotted line goes off and the audio level display "AF" shows full deflection (hissing noise).</p>

If you have accidentally switched off the squelch:

- ▶ Press the UP button to switch the squelch on.


Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

Scanning for, releasing and selecting frequency presets

Menu item	Function of the menu item
Scan New List	Automatically scans for unused receiving frequencies (frequency preset scan). If receiving frequencies are used, they will be locked; if receiving frequencies are unused, they will be released. After the frequency preset scan, you can select an unused frequency preset.
Reset List	Releases all locked frequency presets
Current List	Selects an unused frequency preset

If you call up the "Scan New List" menu item, your receiver scans for unused frequency presets. After the scan, the receiver displays a list of the frequency banks and their unused channels. The frequency bank with the largest number of unused channels is automatically selected.


To perform a frequency preset scan:



You can call up the list containing the frequency banks again by selecting the "Current List" menu item.

Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

Selecting the frequency bank and the channel




When setting up multi-channel systems, please observe the following:


Only the factory-preset frequencies within one frequency bank ("1" to "20") are intermodulation-free. It is vital to observe the notes on frequency selection on page 42.

Overview of the frequency banks and channels:

Frequency bank	Channels	Type
"1" to "20"	up to 32 per frequency bank	System bank: frequencies are factory-preset
"U"	up to 12	User bank: frequencies are freely selectable



Entering a name




Via the "Name" menu item, you can enter a freely selectable name (e.g. the name of the performer) for the receiver.

The name is displayed on the "Receiver Parameters" standard display and can consist of up to eight characters such as:

- letters (without pronunciation marks),
- numbers from 0 to 9,
- special characters and spaces.

To enter a name, proceed as follows:

- ▶ Press the UP/DOWN button to select a character.
- ▶ Press the SET button to change to the next segment/character or to store the complete entry.



Adjusting the audio output level

Adjustment range: -24 dB to +24 dB, adjustable in 3-dB steps

Via the "AF Out" menu item, you can adjust the level of the audio output AF OUT from the receiver to the input of the connected device. The following figures are a guide to the best settings:

Connected device	Guide values for "AF Out"
Line	0 to +18 dB (+24 dB)
Microphone	-24 dB to -6 dB

Gain values greater than +18 dB should only be used when the audio modulation from the transmitter is at a low level, otherwise the audio output of the receiver may become clipped and distorted.

To adjust a gain greater than +18 dB (gain reserve):

- ▶ Adjust a level of +18 dB.
- ▶ Turn the jog dial to the right and hold it in this position for 3 seconds. The next higher value (+21 dB) appears. The audio output level is increased. Using this gain reserve also increases the headphone output level.

Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

Using the equalizer

Via the “Equalizer” menu item, you can change the treble and bass of the audio output signal.

“Flat” (output signal remains unchanged)	“Low cut” (cuts the bass)	“Low Cut/High Boost” (cuts the bass and boosts the treble)	“High Boost” (boosts the treble)

Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

Activating/deactivating the automatic lock mode

The lock mode prevents that the receiver is accidentally switched off or programmed during operation.

The lock mode icon  on the current standard display indicates that the lock mode is activated. For information on how to use the lock mode, refer to page 22.

Menu
Squelch
Easy Setup
Frequency Preset
Name
AF Out
Equalizer
Auto Lock
Advanced
Exit

The extended menu “Advanced Menu”

To get into the extended menu “Advanced Menu”:

- ▶ From the main menu, select “Advanced”.

Advanced Menu
Tune
Guitar Tuner
Pilot Tone
LCD Contrast
Reset
Software Revision
Exit

Setting receiving frequencies for the frequency bank “U”



When you have selected one of the system banks and then select the “Tune” menu, the receiver automatically switches to channel 1 of the frequency bank “U”. In this case, “U.1” briefly appears on the display panel.

Upon delivery, the channels of the frequency bank “U” are not assigned a receiving frequency.

Via the “Tune” menu item, you can set a receiving frequency to be stored in the current channel **or** you can select a different channel in the frequency bank “U” and assign this channel a receiving frequency.




It is vital to observe the notes on frequency selection on page 42.

Setting a receiving frequency for the current channel

- ▶ Press the UP/DOWN button until the “Tune” menu item appears.



- ▶ Press the SET button. The frequency selection appears.



- ▶ Set the desired frequency.



- ▶ Press the SET button. Your settings are stored. You are back to the operating menu.

Selecting a channel and assigning this channel a receiving frequency

- ▶ Press the UP/DOWN button until the "Tune" menu item appears.
- ▶ Keep the SET button pressed until the channel selection appears.



- ▶ Set the desired channel.
 - ▶ Press the SET button. The frequency selection appears.
- ▶ Set the desired frequency.
 - ▶ Press the SET button. Your settings are stored. You are back to the operating menu.

Advanced Menu
Tune
Guitar Tuner
Pilot Tone
LCD Contrast
Reset
Software Revision
Exit

Changing the settings of the guitar tuner

The following settings are available:

Setting	Meaning
"Inactive"	The "Guitar Tuner" standard display is deactivated (see page 24).
"Active"	When selecting the "Guitar Tuner" standard display (see page 24), the receiver is not muted.
"Audio Mute"	When selecting the "Guitar Tuner" standard display (see page 24), the receiver is muted.

Advanced Menu
Tune
Guitar Tuner
Pilot Tone
LCD Contrast
Reset
Software Revision
Exit

Activating/deactivating the pilot tone evaluation

The pilot tone supports the receiver's squelch function and protects against interference due to RF signals from other devices. The transmitter adds an inaudible signal, known as the pilot tone, to the transmitted signal. The receiver detects and evaluates the pilot tone.


Receiver display	Meaning
	The pilot tone evaluation ⑥ is deactivated.
	The pilot tone evaluation ⑥ is activated.
	The pilot tone evaluation ⑥ is activated and the receiver receives a pilot tone from a transmitter.

Devices of the ew 100 G1 series (generation 1) do not support the pilot tone function. Therefore, please observe the following when combining a radio microphone or receiver of the ew 100 G3 series (generation 3) with devices from an earlier evolution wireless generation:

Transmitter	Receiver	Make sure to ...
ew G3/ew G2	ew G3/ew G2	... activate the pilot tone function on both transmitter and receiver.
ew G3	ew G1	... deactivate the pilot tone function on the ew 100 G3 transmitter.
ew G1	ew G3	... deactivate the pilot tone function on the ew 100 G3 receiver.

Advanced Menu	
Tune	
Guitar Tuner	
Pilot Tone	
LCD Contrast	
Reset	
Software Revision	
Exit	


Adjusting the contrast of the display panel



You can adjust the contrast of the display panel in 16 steps.

Advanced Menu	
Tune	
Guitar Tuner	
Pilot Tone	
LCD Contrast	
Reset	
Software Revision	
Exit	

Resetting the settings made in the operating menu



When resetting the settings made in the operating menu, only the selected settings for the pilot tone and for the frequency bank "U" remain unchanged. For an overview of the factory-preset default settings, refer to the supplied frequency information sheet.

Advanced Menu	
Tune	
Guitar Tuner	
Pilot Tone	
LCD Contrast	
Reset	
Software Revision	
Exit	

Displaying the software revision

You can display the current software revision of the receiver.

Synchronizing transmitters with receivers

When synchronizing a transmitter with a receiver, please observe the following:




- ▶ Only use a transmitter and a receiver from the same frequency range (see the type plate on the transmitter and the receiver).
- ▶ Make sure that the desired frequencies are listed in the enclosed frequency information sheet.
- ▶ Make sure that the desired frequencies are approved and legal in your country and, if necessary, apply for an operating license.

Synchronizing a transmitter with the receiver – individual operation

Upon delivery, transmitter and receiver are synchronized with each other.

If, however, you cannot establish a transmission link between transmitter and receiver, you have to synchronize the channels of the devices.

- ▶ With the receiver, perform a frequency preset scan to scan the frequency banks for unused channels (“Scan New List”, see page 34). Then “Sync” appears on the display panel of the receiver.



- ▶ Synchronize a transmitter with the receiver via the infra-red interface (see page 20). This establishes a transmission link between the transmitter and the receiver.

Alternatively, you can set the channel on the transmitter manually:

- ▶ Make sure that you set the transmitter to the same frequency bank and the same channel as the receiver (see the instruction manual of the transmitter).

Synchronizing transmitters with receivers – multi-channel operation



In order to ensure an intermodulation-free transmission, use the same frequency bank for all transmission links.

- ▶ Switch off all transmitters of your system that are to be automatically configured.
Channels used by switched-on transmitters are displayed as “used”.
- ▶ With one of the receivers, perform a frequency preset scan to scan the frequency banks for unused channels (“Scan New List”, see page 34). Then “Sync” appears on the display panel of the receiver.



- ▶ Switch one of the transmitters on.
- ▶ Synchronize this transmitter with the receiver via the infra-red interface (see page 20).
This establishes a transmission link between the transmitter and the receiver.
- ▶ Repeat for the remaining transmitter and receiver pairs as described above. Leave those transmitters switched on that are already linked to a receiver.
Your multi-channel system is now set up.

Alternatively, you can set the channel on the transmitter manually:

- ▶ Make sure that you set the transmitter to the same frequency bank and the same channel as the receiver.
For information on the setting options of the transmitter, refer to the instruction manual of the transmitter.

You can also freely select the receiving frequencies and store these frequencies in the frequency bank “U”.



If you are using frequencies from the frequency banks “U”, it might be that the receiving frequencies are not intermodulation-free.

To ensure that the desired frequencies are intermodulation-free:

- ▶ Contact your Sennheiser partner (see www.sennheiser.com).

If you want to use the frequency bank "U":

- ▶ Make sure to use receivers from the same frequency range (see page 5 and the type plates of the devices).
- ▶ Only use frequencies that are approved and legal in your country.
- ▶ On one of the receivers, select a channel within the frequency bank "U" (see page 39).
- ▶ Assign this channel one of the receiving frequencies (see page 39).
- ▶ Synchronize a transmitter with the receiver (see page 20).

OR

- ▶ Manually set the transmitter to the same channel and frequency that you set on the receiver.
- ▶ Repeat for the remaining transmitters and receivers as described above.

Cleaning the receiver

CAUTION!

Liquids can damage the electronics of the receiver!

Liquids entering the housing of the receiver can cause a short-circuit and damage the electronics.

- ▶ Keep all liquids away from the receiver.
-
- ▶ Before cleaning, disconnect the receiver from the mains.
 - ▶ Use a cloth to clean the receiver from time to time. Do not use any solvents or cleansing agents.

Recommendations and tips

... for optimum reception

- Transmission range depends to a large extent on location and can vary from about 10 m to about 150 m. There should be a “free line of sight” between transmitting and receiving antennas.
- If, with the EM 100 G3 receiver, reception conditions are unfavourable, you should use two remote antennas which are connected via antenna cable.
- To avoid overloading the receiver, observe a minimum distance of 5 m between transmitting and receiving antennas.
- Observe a minimum distance of 50 cm between receiving antennas and metal objects (such as cross members or reinforced-concrete walls). Align the antennas upwards in a V-shape.

... for multi-channel operation

- Each of the frequency banks “1” to “20” accommodates factory-preset receiving frequencies which are intermodulation-free. For possible frequency combinations, please refer to the supplied frequency information sheet.
- The channels in the frequency bank “U” can be assigned freely selectable frequencies (see page 39).
- When using several transmitters simultaneously, interference can be avoided by maintaining a minimum distance of 20 cm between two transmitters.
- Use accessories recommended by Sennheiser for multi-channel applications (see page 49).

If a problem occurs ...

Problem	Possible cause	Possible solution
Receiver cannot be operated, "Locked" appears on the display panel	Lock mode is activated	Deactivate the lock mode (see page 22).
No operation indication	No mains connection	Check the connections of the mains unit.
No RF signal	Transmitter and receiver are not on the same channel	Set the transmitter and receiver to the same channel. To do so, use the synchronization function (see page 20).
	Transmission range is exceeded	Check the squelch threshold setting (see page 33). Reduce the distance between transmitter and receiving antennas.
RF signal available, no audio signal, "MUTE" appears on the display panel	Receiver is muted	Cancel the muting on the receiver (see page 23).
	Transmitter is muted or doesn't transmit a pilot tone	Cancel the muting on the transmitter (see the instruction manual of the transmitter).
		Activate the pilot tone transmission on the transmitter (see the instruction manual of the transmitter).
		Deactivate the pilot tone evaluation on the receiver (see page 40).
Receiver's squelch threshold is adjusted too high	Reduce the squelch threshold (see page 33). Reposition the antennas.	
Audio signal has a high level of background noise	Transmitter sensitivity is adjusted too low	Adjust the transmitter sensitivity correctly (see the instruction manual of the transmitter).
Audio signal is distorted	Transmitter sensitivity is adjusted too high	Adjust the transmitter sensitivity correctly (see the instruction manual of the transmitter).
	Receiver's audio output level is adjusted too high	Reduce the audio output level (see page 36).

Problem	Possible cause	Possible solution
No access to a certain channel	During scanning, an RF signal has been detected on this channel and the channel has been locked	Set the transmitter operating on this channel to a different channel and redo the frequency preset scan (see page 34).
	During scanning, a transmitter of your system operating on this channel has not been switched off	Switch the transmitter off and redo the frequency preset scan (see page 34).
During the sound-check, only one diversity display (I or II) appears on the display panel	One of the antennas is not correctly connected	Check the antenna cable or the antenna.
	Antennas are not optimally positioned	Reposition the antennas.
None of the diversity displays I or II appears on the display panel	Receiver's squelch threshold is adjusted too high	Reduce the squelch threshold (see page 33).
	Transmitter's RF signal is too weak	Reduce the distance between transmitter and receiver.

If a problem occurs that is not listed in the above table or if the problem cannot be solved with the proposed solutions, please contact your local Sennheiser partner for assistance.

To find a Sennheiser partner in your country, search at www.sennheiser.com under "Service & Support".

Accessories and spare parts

The following accessories are available from your specialist dealer:

Cat. No. **Product name and description**

503167 GA 3 rack adapter

009912 AM 2 antenna front mount kit (for GA 3 rack adapter)

503165 ASA 1 active antenna splitter, 2 x 1:4,
for connecting four EM 100 G3 to two antennas/antenna boosters

503158 NT 1-1 EU
Mains unit for powering the ASA 1 antenna splitter or the L 2015 charger,
EU version

503873 NT 1-1 US
Mains unit for powering the ASA 1 antenna splitter or the L 2015 charger,
120 V version

503874 NT 1-1 UK
Mains unit for powering the ASA 1 antenna splitter or the L 2015 charger,
UK version

503157 NT 2-3 EU
Mains unit for powering the EM 100 G3 stationary receiver, EU version

503870 NT 2-3 US
Mains unit for powering the EM 100 G3 stationary receiver, 120 V version

503871 NT 2-3 UK
Mains unit for powering the EM 100 G3 stationary receiver, UK version

Antennas

004645 A 1031 antenna, broadband, omni-directional

003658 A 2003 antenna, broadband, directional

Antenna boosters for ASA 1

502567 AB 3-A: 516–558 MHz

502572 AB 3-G: 566–608 MHz

502568 AB 3-B: 626–668 MHz

502569 AB 3-C: 734–776 MHz

502570 AB 3-D: 780–822 MHz

502571 AB 3-E: 823–865 MHz

Antenna cables

002324 GZL 1019-A1 coaxial cable, type RG 58, BNC to BNC, 1 m

002325 GZL 1019-A5 coaxial cable, type RG 58, BNC to BNC, 5 m

002326 GZL 1019-A10 coaxial cable, type RG 58, BNC to BNC, 10 m

Specifications

RF characteristics

Modulation	wideband FM
Frequency ranges	516–558, 566–608, 626–668, 734–776, 780–822, 823–865 MHz (A–E, G, see page 4)
Receiving frequencies	1,680 receiving frequencies, tuneable in steps of 25 kHz
	20 frequency banks, each with up to 12 factory-preset channels, intermodulation-free
	1 frequency bank with up to 12 user programmable channels
Switching bandwidth	42 MHz
Nominal/peak deviation	± 24 kHz/ ± 48 kHz
Receiver principle	true diversity
Sensitivity (with HDX , peak deviation)	$< 2 \mu\text{V}$ for 52 dBA _{rms S/N}
Adjacent channel rejection	typ. ≥ 65 dB
Intermodulation attenuation	typ. ≥ 65 dB
Blocking	≥ 70 dB
Squelch	Off, Low: 5 dB μV , Middle: 15 dB μV , High: 25 dB μV
Pilot tone squelch	can be switched off
Antenna inputs	2 BNC sockets

AF characteristics

Compander system	Sennheiser HDX
EQ presets	
Preset 1: "Flat"	
Preset 2: "Low Cut"	-3 dB at 180 Hz
Preset 3: "Low Cut/High boost"	-3 dB at 180 Hz +6 dB at 10 kHz
Preset 4: "High Boost"	+6 dB at 10 kHz

Specifications

S/N ratio (1 mV, peak deviation)	≥ 110 dBA
THD	≤ 0.9%
AF output voltage (at peak deviation, 1 kHz AF)	¼" (6.3 mm) jack socket (unbalanced): +12 dBu XLR socket (balanced): +18 dBu
Adjustment range of audio output level	48 dB, adjustable in steps of 3 dB +6 dB gain reserve

Overall device

Temperature range	-10°C to +55°C
Power supply	12 V ===
Current consumption	300 mA
Dimensions	approx. 190 mm x 212 mm x 43 mm
Weight	approx. 980 g

Type approvals

In compliance with

Europe	 EMC EN 301489-1/-9 Radio EN 300422-1/-2 Safety EN 60065
USA	 47 CFR 15 subpart B

Approved by

Canada	Industry Canada RSS 123 IC: 2099A-G3EM100
--------	--

Mains unit*

	NT 2-1	NT 2-3
Input voltage	110 V~ or 230 V~, 50/60 Hz	100 to 240 V~, 50/60 Hz
Power/Current consumption	9 VA	max. 120 mA
Output voltage	13 V ===	12 V ===
Secondary output current	300 mA	400 mA
Energy efficiency level	IV	IV
Temperature range	-10°C to +40°C	-10°C to +40°C




* depending on country variant

In compliance with (mains unit)

Europe	 EMC EN 55022, EN 55024, EN 55014-1/-2 Safety EN 60065
USA	 47 CFR 15 subpart B
Canada	ICES 003

The mains unit is certified in accordance with the legal safety requirements of Europe, the United States, Canada, Russia and Japan.

Connector assignment

Audio			Other connectors
1/4" (6.3 mm) stereo jack plug, balanced	XLR-3F connector, balanced	1/4" (6.3 mm) mono jack plug, unbalanced	DC connector for power supply
			

Manufacturer Declarations

Warranty

Sennheiser electronic GmbH & Co. KG gives a warranty of 24 months on this product.

For the current warranty conditions, please visit our website at www.sennheiser.com or contact your Sennheiser partner.

In compliance with the following requirements

- RoHS Directive (2002/95/EC)
- WEEE Directive (2002/96/EC)



Please dispose of the receiver at the end of its operational lifetime by taking it to your local collection point or recycling center for such equipment.

CE Declaration of Conformity

- **CE 0682**
- R&TTE Directive (1999/5/EC), EMC Directive (2004/108/EC), Low Voltage Directive (2006/95/EC)

The declarations are available at www.sennheiser.com.

Before putting the device into operation, please observe the respective country-specific regulations.

Statements regarding FCC and Industry Canada

This device complies with Part 15 of the FCC Rules and with RSS-210 of Industry Canada. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This class B digital device complies with the Canadian ICES-003.

Changes or modifications made to this equipment not expressly approved by Sennheiser electronic Corp. may void the FCC authorization to operate this equipment.

Before putting the device into operation, please observe the respective country-specific regulations!

Index

Activating/deactivating

- lock mode (Auto Lock) 37
- pilot tone evaluation 40

Adjusting

- audio output level (AF Out) 36
- contrast (LCD Contrast) 41
- squelch threshold (Squelch) 33

Advanced Menu (extended menu)

- overview 27
- settings 38

AF Out (adjusting the audio output level) 36

Amplifier/Mixing console, connecting 17

Antennas, mounting 13

Audio signal, muting (Mute) 23

Auto Lock (activating/deactivating the lock mode) 37

Buttons (function of the ~) 25

Channel

- assigning a frequency 39
- overview 5
- selecting (Easy Setup) 34, 42
- selecting (Frequency Preset) 35

Cleaning (receiver) 45

Connecting

- amplifier/Mixing console 17
- mains unit 18

Current List (selecting an unused frequency preset) 34

Deactivating (lock mode temporarily) 22

Displays

- adjusting the contrast (LCD Contrast) 41
- overview 9
- standard displays 24

Easy Setup (submenu)

- overview 26
- settings 34

Equalizer (modifying the frequency response) 37

Frequency

- preset frequencies 5
- ~ ranges 5
- selecting (Frequency Preset) 35
- selecting ~ presets 35
- setting a receiving frequency 38

Frequency bank

- overview 5
- selecting (Easy Setup) 34, 42
- selecting (Frequency Preset) 35
- ~ system 5

Frequency Preset (selecting a frequency bank/channel) 35

Frequency presets

- releasing (Reset List) 34
- searching for unused ~ (Scan New List) 34, 42
- selecting (Current List) 34

Guitar Tuner

- changing the settings 39
- tuning a guitar 30

Infra-red transmission 20

LCD Contrast (contrast of the display panel) 41

Lock mode

- activating/deactivating (Auto Lock) 37
- deactivating temporarily 22

Locked (lock mode activated) 22

Mains unit, connecting 18

Menu (main menu)

- overview 26
- settings 33

Mixing console/amplifier, connecting 17

- Mounting**
 - antennas 13
 - receiver 11
- Multi-channel operation** 43
- Mute (muting the audio signal)** 23
- Muting (audio signal)** 23
- Name (entering a name)** 36
- Operating menu, using** 28
- Pilot tone evaluation, activating/deactivating** 40
- Rack mounting**
 - one receiver 14
 - two receivers 15
- Receiver**
 - cleaning 45
 - mounting into a rack 11
 - ~ parameters (standard display) 9
 - placing onto a flat surface 11
 - switching on/off 19
 - synchronizing with transmitter 20, 42
- Receiving frequency**
 - selecting (Frequency Preset) 34
 - setting (Tune) 38
- Reception, optimizing** 46
- Reset List (releasing all locked frequency presets)** 34
- RF (Radio Frequency)** 9
- RX Mute On/Off (muting the audio signal)** 23
- Scan New List (frequency preset scan)** 34, 42
- Setting up**
 - multi-channel system 43
 - transmission link 42
- Settings**
 - equalizer 37
 - guitar Tuner 39
- Software Revision (displaying the software revision)** 41
- Soundcheck, doing** 30
- Squelch (adjusting the squelch)** 33
- Switching on/off (receiver)** 19
- Synchronizing (transmitter with receiver)**
 - 20, 42
- Transmission link, setting up** 42
- Transmitter, synchronizing with receiver**
 - 20, 42
- Troubleshooting** 47
- Unlock (deactivating the lock mode)** 22
- Using**
 - guitar Tuner 30
 - operating menu 28
 - receiver 19

Sennheiser electronic GmbH & Co. KG
Am Labor 1, 30900 Wedemark, Germany
www.sennheiser.com

Printed in Germany
Publ. 01/09
529663/A01

evolutionwireless 