



SENNHEISER EW-352 G2 UHF Wireless Microphone Set



Sennheiser EW 352 G2 Features:

- 1440 tunable UHF frequencies for interference-free reception
- Absolutely reliable transmission and extended range due to high RF output power
- High-quality true diversity reception
- Pilot tone squelch for eliminating RF interference when transmitter is turned off
- Automatic frequency scan feature searches for available frequencies
- Transmitter and receiver with rugged metal housings
- Rack mount included
- Transmitter has contacts for recharging the BA 2015 rechargeable battery pack directly in the transmitter
- Transmitter with backlit display (lights up when a button is pushed)
- Receiver features user-friendly menu operation via two-colour backlit graphics display (green = OK; red = warning)
- Lock function avoids accidental changing of settings
- HDX compander for crystal-clear sound
- 4-step battery status display, also transmitted to receiver
- Mute function for the transmitter
- Wide range of accessories adapts the system to any requirement
- EM 300 G2 rack-mount receiver, SK 300 G2 bodypack transmitter, ME 3 headset, GA 2 rack mount, NT 2-1 power supply unit, 2 x AA batteries and Operating instructions included with this set

Sennheiser EW 352 G2 Specifications:

- Transmission/receiving frequencies: 1440
- Presets: 8
- Switching bandwidth: 36
- Peak deviation: +/- 48 kHz
- Comander: HDX
- Frequency response (microphone): 40 – 18000 Hz
- Signal-to-noise ratio: 112 dB(A)
- THD, total harmonic distortion: 0.9 %
- In compliance with ETS 300422 , ETS 300445 , CE , FCC
- Antenna connector: 2 BNC, 50 Ohm
- Audio-XLR connector: 6,3 mm
- Audio output level (balanced) XLR: +18 dBu max
- Audio output level (unbalanced) Jack: +12 dBu max
- Power supply: 10.5 – 16 V DC
- Dimensions (Receiver): 212 x 145 x 38 mm
- Weight (Receiver): 1100 g
- RF output power: 30 mW
- Power supply: 2x 1.5 V battery AA (Mignon)
- Operating time (transmitter): 8 h
- Input voltage range mic: 1.8 V
- Input voltage range line: 2.4 V
- Dimensions (Transmitter): 82 x 64 x 24 mm
- Weight (Transmitter): 158 g
- Transducer; Microphone type: elektret
- AF sensitivity: 1.6 mV/Pa
- Sound pressure level (SPL): 150 dB(SPL) max.
- Pick-up pattern: Super-Cardioid

The Sennheiser EW 352 G2 system is feature packed, professional and an ideal choice for hands-free vocal and speech applications.