









## **HD 25 Dynamic Headphone**

The closed-back HD 25s are purpose-designed, professional monitoring headphones offering high attenuation of background noise. Capable of handling very high sound pressure levels and of extremely robust construction, these headphones perform exceptionally well in high-noise environments, e.g. ENG, sound reinforcement, studio monitoring and audio equipment testing. The capsule is rotatable for one-ear listening. Ideal monitoring headphones for cameramen and

#### Features—Benefits

- · High sensitivity due to lightweight aluminum voice coils
- · Very good attenuation of background noise
- · Low weight
- · Adjustable split headband for exceptional comfort
- · Replaceable, single-sided steel connection cable
- · Great sound
- · Great for mixing in noisy environments
- · Virtually a custom fit
- · Easily field-servicable

#### **Technical Data**

Weight (without cable)

Frequency response 16-22,000 Hz -3 dB Transducer principle dynamic, closed Nominal impedance  $70 \Omega$ Characteristic SPL at 1 kHz 1 120 dB Load rating 200 mW THD < 0.3 % Ear coupling supraural Contact pressure approx. 3 N

Connector 1/8" stereo mini jack plug with adapter

to 1/4" stereo jack plug

approx. 4.93 oz

Connection cable 1.5 m, single-sided steel cable

## **Optional Accessories**

Stereo volume control HZR 6

continued



## **Supplied Accessories**

1 cable clip

# **Optional Accessories**

Stereo volume control

HZR 6

Replacement Parts

Ear pads (1 pair)

Velour ear pads (optional) (1 pair)

Connection cable

#### **Product Compatibility**

For monitoring, recording and outdoor applications

### **Architect's Specifications**

The headphone shall be a closed dynamic professional headphone for use in noisy environments, with high sensitivity and a sound pressure level of 120 dB and shall have the following: Adjustable headband and earpieces for professional monitoring applications. Frequency response 16 Hz–22 kHz, total harmonic distortion < 0.3 %, nominal impedance 70  $\Omega$ , load rating 0.2 W. 1.5 m steel cable with 1/8" right-angled stereo jack plug with adapter to 1/4" jack plug. The headphone shall be a Sennheiser HD 25.

Sennheiser Electronic Corporation, 1 Enterprise Drive, Old Lyme, CT 06371
Telephone: 860-434-9190 • Fax: 860-434-1759 • Web: http://www.sennheiserusa.com
Sennheiser Mexico: Av. Xola 613, PH6, Col. Del Valle 03100, Mexico, DF. Telephone: (525) 639-0956. Fax: (525) 639-9482
Sennheiser Canada: 221 Labrosse Ave, Pte-Claire, PQ H9R 1A3. Telephone: 514-426-3013. Fax: 514-426-3953
Manufacturing Plant: Am Labor 1, 30900 Wedemark, Germany