

# C411 PP

**AKG**<sup>®</sup>  
by HARMAN

HIGH-PERFORMANCE MINIATURE CONDENSER VIBRATION PICKUP



## HIGHLIGHTS

**Condenser transducer in sealed enclosure**  
for clear and uncolored sound

**Ultralight vibration pickup**  
does not change the balance of the instrument

## KEY MESSAGE

The C411 is a miniature vibration pickup for acoustic guitar, mandolin, violin and most other string instruments. Its integrated condenser capsule will reproduce the sound of the instrument clearly and without coloration. The C411 ultralight pickup (18g/0.6oz) can be easily attached on or near the bridge with the included nonmarking, solvent-free adhesive pad without changing the balance of the instrument. The C411 is available in two versions. The C411 PP features a MPAV standard XLR connector while the C411 L provides a professional three-pin mini XLR connector that fits the body-pack transmitters of all AKG wireless microphone systems.

## INCLUDED ACCESSORIES

### Microphone Bag



**AKG ACOUSTICS, U.S.** 8400 BALBOA BOULEVARD, NORTHRIDGE, CA 91329, U.S.A.  
**AKG ACOUSTICS GMBH** LAXENBURGER STRASSE 254, 1230 VIENNA, AUSTRIA

© 2017 HARMAN International Industries, Incorporated. All rights reserved. AKG is a trademark of AKG Acoustics GmbH, registered in the United States and/or other countries. Features, specifications and appearance are subject to change without notice.

[www.ake.com/pro](http://www.ake.com/pro)

---

|                             |   |
|-----------------------------|---|
| Type:                       | pre-polarized condenser transducer                        |
| Polar pattern:              | Figure 8  |
| Frequency range:            | 10 – 18,000 Hz  |
| Sensitivity:                | 1 mV/ms <sup>-2</sup> (vibration pickup)                  |
| Impedance at 1,000 Hz:      | 200 Ω, unbalanced   |
| Recommended load impedance: | ≥1,000 ohms   |
| Max. SPL for 1%/3% THD:     | 96 dB / 103 dB  |
| Powering:                   | C411 <sup>III</sup> PP: 9 to 52 V universal phantom power |

---

|                         |   |
|-------------------------|---|
| Current consumption:    | approx. 2.2 mA  |
| Cable length/Connector: | C411 <sup>III</sup> PP: 3 m (10 ft.) / 3-pin male XLR |

---

|                      |  |
|----------------------|--|
| Finish:              | matte black  |
| Dimensions:          | 27 x 14 x 9.5 mm (1 x 0.6 x 0.4 in.).                  |
| Net/shipping weight: | C411 <sup>III</sup> PP: 98 g (3.5 oz.) / 225 g (8 oz.) |

---