

VS-88A

8x8 Balanced Stereo Audio Matrix Switcher



The VS-88A is a high-performance matrix switcher for balanced stereo audio signals. It can route any or all inputs to any or all outputs simultaneously

FEATURES

S/N Ratio - 84dB unweighted (1Vpp)

Control - Front panel, RS-232 (K-Router™ Windows®-based Kramer software is included), RS-485 Take Button - Executes multiple switches all at once

Memory Locations - Stores multiple switches as presets to be recalled and executed when needed Worldwide Power Supply - 100-240V AC



TECHNICAL SPECIFICATIONS

INPUTS:	8 balanced stereo audio, +4dBu/33k Ω on detachable terminal blocks
OUTPUTS:	8 balanced stereo audio, +4dBu/50 Ω (20Vpp max) on detachable terminal blocks
AUDIO BANDWIDTH (-3dB):	100kHz
AUDIO S/N:	84dB unweighted (1Vpp)
CONTROL:	22 front panel buttons, RS-232 and RS-485 control interface
AUDIO THD:	0.025% (1Vpp, 1kHz)
2nd HARMONIC:	0.013%
MAX. AUDIO:	>20dBu
INDICATORS:	8-character display on the front panel
POWER CONSUMPTION:	115/230V AC, 50/60Hz, 16VA max
INCLUDED ACCESSORIES:	Power cord
Product Dimension	19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H
Product Weight	3.0kg (6.6lbs) approx
Shipping Dimension	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H
Shipping Weight	3.8kg (8.3lbs) approx

