



VS-88H2

8x8 4K HDR HDCP 2.2 Matrix Switcher with Digital Audio Routing

| HDMI | Ethernet - RJ-45



VS-88H2 is a high-performance 8x8 matrix switcher for 4K@60Hz (4:4:4) HDR signals and digital audio routing. It reclocks and equalizes the signals and can route any one of 8 HDMI, HDCP-compliant sources (selectable) to any or all outputs simultaneously. VS-88H2 offers unmatched audio flexibility where any embedded digital audio input can be routed to any digital output in addition to eight ARC sources to produce an equivalent 16x16 audio matrix

FEATURES

High-Performance AV Matrix - Switches 8 4K@60Hz (4:4:4), HDR, HDMI, HDCP (2.2/1.4)-compliant signals to 8 4K@60Hz (4:4:4), HDR, HDMI, HDCP (2.2/1.4)-compliant outputs at up to 18G data rate. Featuring Kramer re-Klocking™ and Equalization Technology that rebuilds the digital signal to travel longer distances. Note: For optimum range and performance, use recommended Kramer cables

HDMI Support - Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels as specified in HDMI 2.0

Independent Audio Routing - Any embedded digital audio input can be routed to any digital output, in addition to ARC sources, to produce an equivalent 16x16 audio matrix (8 embedded digital inputs + 8 ARC inputs and 8 digital outputs + 8 ARC outputs)

Easy Step-In Collaboration Function - When used with a Kramer Step-In enabled switcher, just plug in your device and press the Step-In button. Your device becomes the active signal on the main display

EDID Management - Individual EDID management per input. Captures and stores the EDID from a display device

Flexible Content Protection - Selectable HDCP per input

Quick Access to Common Configurations - Save up to 16 preset configurations

Smart Switching - Active source & acceptor detection. Automatic input selection based on priority selection or last connected input

Embedded Pattern Generator - With selectable patterns

Convenient Unit Control and Configuration Options - Local control via front panel switching, memory, lock and EDID buttons, and Input/Output LED display. Distance control via user-friendly embedded web pages via the Ethernet, Protocol 3000 API, and RS-232 serial commands transmitted by a PC, touch screen system or other serial controller

Cost-Effective Maintenance - Input selection indicators facilitate easy local maintenance and troubleshooting. Firmware upgrade via Ethernet or mini USB

Easy Installation - 19" enclosure for rack mounting in a 1U rack space with included rack ears and universal 100-240V AC power supply



TECHNICAL SPECIFICATIONS

Inputs	8 HDMI: On female HDMI connectors
Outputs	8 HDMI: On female HDMI connectors
Ports	1 Ethernet: On an RJ-45 connector 1 RS-232: On a 3-pin terminal block connector 1 USB: On a USB type A connector, for powering an external device 1 USB: On a mini USB connector, for firmware upgrade or communication with a PC or serial controller
Video	HDMI Support: Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels as specified in HDMI 2.0 Content Protection: HDCP 2.2 Max. Output Resolution: 4K@60Hz (4:4:4)
User Interface	Control: Input/output selection, mute, test pattern, memory, front panel lock, buttons. RS-232 serial commands transmitted by a PC, touch screen system or other serial controller, embedded web pages via LAN for configuration and control Indicators: Input/output LCD display
Power	Source: 100-240V AC 50/60Hz Consumption: 600mA
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RH (non-condensing)
Accessories	Included: Rack ears, rubber feet, power cord
Product Dimensions	43.64cm x 18.30cm x 4.36cm (17.18" x 7.20" x 1.72") W, D, H
Product Weight	2.4kg (5.2lbs) approx
Shipping Dimensions	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
Shipping Weight	3.3kg (7.3lbs) approx

