



Tourguide 2020-D

HDE 2020-D-II



The HDE 2020-D stethoset TourGuide receiver is comfortable to wear and integrates both the receiver and headphones. The powerful battery ensures up to 8 hours operating time.

The stethoset receiver automatically deactivates itself the moment that it is taken off, thus battery life will be preserved. Tour participants will be able to individually adjust the volume through a rotary control on the receiver, without the need to even take the device off.

The LC display provides information of volume, battery status, quality of reception and the channel being listened to. Channels can easily be set and adjusted by using the middle buttons.

FEATURES

- Digital RF signal reception
- Intuitive operating concept
- 8 hours battery life
- Sturdy earbows
- Backlit LC display
- Large rotary volume control

DELIVERY INCLUDES

- HDE 2020-D-II
- Instruction manual

SPECIFICATIONS

| | |
|--------------------------|---|
| Modulation | 2 FSK |
| Frequency range | 863 – 865 MHz |
| Frequency range (US) | 926 – 928 MHz |
| Channels | |
| Tourguide mode: | 6 in parallel |
| Conference mode: | 8 in parallel |
| AF frequency response | 100 – 7,000 Hz |
| Headphone output power | – |
| Min. headphone impedance | 32 Ω |
| THD at 1 kHz | < 1 % |
| Operating time | typ. 8 h |
| Power supply | Lithium-Polymer rechargeable battery, 830 mAh |
| Temperature range | 0 – 50 °C |
| Dimensions | 245 x 125 x 20 mm |
| Weight | approx. 73 g |

PRODUCT VARIANTS

| | |
|------------------|-----------------|
| HDE 2020-D-II-US | Art. no. 504797 |
| HDE 2020-D-II | Art. no. 504796 |

ACCESSORIES

| | | |
|-----------------|----------------------|-----------------|
| EZL 2020-20 L | Charging case | Art. no. 500542 |
| L 2021-40 | 19" charger rack | Art. no. 502037 |
| OP - HDE 2020 | Earbuds, black | Art. no. 531435 |
| OP - HDE 2020-D | Earbuds, luminescent | Art. no. 520379 |



Tourguide 2020-D HDE 2020-D-II

DIMENSIONS

